

BLACK & GALVANIZED
STEEL TUBES CONFORMING TO IS:1239(I) EQUIVALENT TO BS:1387
& STRUCTURAL TUBES CONFORMING TO IS:1161

SERIES			LIGHT					MEDIUM					HEAVY				
NOMINAL BORE		O.D.	OUTSIDE DIA.		WALL THICK.	WEIGHT		OUTSIDE DIA.		WALL THICK.	WEIGHT		OUTSIDE DIA.		WALL THICK.	WEIGHT	
INCH	mm	mm	(MIN.) mm	(MAX.) mm	mm	P/E Kg/m	S/S Kg/m	(MIN.) mm	(MAX.) mm	mm	P/E Kg/m	S/S Kg/m	(MIN.) mm	(MAX.) mm	mm	P/E Kg/m	S/S Kg/m
1/2	15	21.3	21.0	21.4	2.0	0.947	0.956	21.0	21.8	2.6	1.21	1.22	21.0	21.8	3.2	1.44	1.45
3/4	20	26.9	26.4	26.9	2.3	1.38	1.39	26.5	27.3	2.6	1.56	1.57	26.5	27.3	3.2	1.87	1.88
1	25	33.7	33.2	33.8	2.6	1.98	2.00	33.3	34.2	3.2	2.41	2.43	33.3	34.2	4.0	2.93	2.95
1-1/4	32	42.2	41.9	42.5	2.6	2.54	2.57	42.0	42.9	3.2	3.10	3.13	42.0	42.9	4.0	3.79	3.82
1-1/2	40	48.3	47.8	48.4	2.9	3.23	3.27	47.9	48.8	3.2	3.56	3.60	47.9	48.8	4.0	4.37	4.41
2	50	60.3	59.6	60.2	2.9	4.08	4.15	59.7	60.8	3.6	5.03	5.10	59.7	60.8	4.5	6.19	6.26
2-1/2	65	76.1	75.2	76.0	3.2	5.71	5.83	75.3	76.6	3.6	6.42	6.54	75.3	76.6	4.5	7.93	8.05
3	80	88.9	87.9	88.7	3.2	6.72	6.89	88.0	89.5	4.0	8.36	8.53	88.0	89.5	4.8	9.90	10.10
4	100	114.3	113.0	113.9	3.6	9.75	10.00	113.1	115.0	4.5	12.20	12.50	113.1	115.0	5.4	14.50	14.80
5	125	139.7	-	-	4.5	15.00	-	138.5	140.8	4.8	15.90	16.40	138.5	140.8	5.4	17.90	18.40
6	150	165.1	-	-	4.5	17.80	-	163.9	166.5	4.8	18.90	19.50	163.9	166.5	5.4	21.30	21.90
6	150	168.3	-	-	4.5	18.20	-	-	-	4.8	19.40	-	-	-	H1-5.4	21.70	-
6	150	168.3	-	-	-	-	-	-	-	-	-	-	-	-	H2-6.3	25.20	-
7	175	193.7	-	-	4.8	22.40	-	-	-	5.4	25.10	-	-	-	5.9	27.30	-
8	200	219.1	-	-	4.8	25.40	-	-	-	5.6	29.50	-	-	-	5.9	31.00	-
10	250	273.0	-	-	-	-	-	-	-	-	-	-	-	-	5.9	38.90	-
12	300	323.9	-	-	-	-	-	-	-	-	-	-	-	-	6.3	49.30	-
14	350	355.6	-	-	-	-	-	-	-	-	-	-	-	-	8.0	68.60	-

- NOTE: (I) IS:1239 & BS:1387 COVERS SIZES UPTO 100 mm NB ALL SERIES, 125 & 150 mm NB MEDIUM & HEAVY SERIES, PLAIN END & SCREWED AND SOCKETED ENDS.
 (II) IS:1161 covers all sizes Plain End only.
 (III) IS:1161 O.D. Tolarence will be as per dimension tolerance table, above table min/max O.D. applicable for IS:1239 only.
 (IV) Hydro test Pressure - 5 MPa (IS:1161 Hydro Test not required.)

** ERW PIPES FOR WATER & SEWAGE CONFORMING TO IS:3589**
& WATER WELL CASING CONFORMING TO IS:4270

SIZE		CONVENTIONAL MASS PER UNIT LENGTH (Kg/m)																	
NB	OD	WALL THICKNESS (mm)																	
mm	mm	3.20	3.60	4.00	4.30	4.65	4.85	5.00	5.20	5.40	5.60	6.00	6.35	6.40	7.00	7.10	8.00	9.50	10.00
100	114.30	-	-	-	-	-	-	13.48	-	14.50	-	16.02	-	-	-	-	-	-	-
125	141.30	-	-	-	-	-	-	16.81	-	18.10	-	20.02	-	-	-	-	-	-	-
150	168.30	13.03	14.62	16.21	17.39	18.77	19.55	20.13	20.91	21.69	-	24.01	25.36	25.55	27.84	28.22	-	-	-
175	193.70	-	16.88	18.71	20.08	21.68	22.59	23.27	24.17	25.07	-	27.77	29.34	29.56	32.23	32.67	36.63	-	-
200	219.10	-	19.13	21.22	22.78	24.59	25.62	26.40	27.43	28.46	29.48	31.53	33.31	33.57	36.61	37.12	41.65	49.10	51.56
250	273.10	-	23.93	26.54	28.50	30.78	32.08	33.06	34.35	35.65	36.94	39.52	41.77	42.09	45.93	46.57	52.30	61.75	64.88
300	323.90	-	-	31.55	33.89	36.61	38.16	39.32	40.87	42.41	43.96	47.04	49.73	50.11	54.70	55.47	62.32	73.65	77.41
350	355.60	-	-	34.68	37.25	40.24	41.95	43.23	44.93	46.63	48.33	51.73	54.69	55.11	60.18	61.02	68.57	81.08	85.22

- NOTE: (I) IS:4270 covers Pipe size 100 mm to 350 mm NB & IS:3589 covers Pipe size 168.3 mm OD to 355.6 mm OD.
 (II) IS:4270 covers Wall Thickness upto 10 mm.
 (III) Other thickness may be supplied as per agreement.
 (IV) Max. Hydro Test Pressure IS:3589 -5 MPa, IS:4270 - 7 MPa.